



#### DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq Yd:	No Minimum
Surface Texture:	Textured Patterned Loop
Gauge:	1/12 (47.00 rows per 10 cm)
Tufted Pile Weight:	17.0 oz. per sq. yd. (576 g/m <sup>2</sup> )
Finished Pile Thickness:	.107" (2.72 mm)
Stitches Per Inch:	12.4 (48.82 per 10 cm)
Dye Method:	Solution Dyed
Fiber Type:	Duracolor® Tricor Premium Nylon
Fiber Technology:	Duracolor® by Mohawk Group's Stain Resistant System. Passes GSA requirements for permanent stain resistant carpet.
Stain Release Technology:	Permanent, Built into Fiber
Soil Release Technology:	EcoSentry Soil Protection
Density:	5,719
Weight Density:	97,233
Backing Material:	EcoFlex NXT
Alternate Backing:	EcoFlex AIR - No Minimum Required
Installation Method:	Quarter Turn, Vertical Ashlar, Brick Ashlar, Monolithic, Multi Directional
Size:	24" x 24" (.6096 m x .6096 m)
Pattern Repeat:	Not Applicable

#### SUSTAINABILITY


Pre-Consumer Recycled Content:	59%
NSF 140:	EcoFlex NXT - NSF 140 Gold
Indoor Air Quality:	CRI Green Label Plus GLP1171
Declare Label:	Declared Red List Free

#### PERFORMANCE


Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
Foot Traffic Recommendation TARR:	Severe
GSA Stain Release Rating:	Pass

#### SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Duracolor Stain Warranty, Lifetime Static, Lifetime Duracolor Stain Warranty
-------------	--



565  
Blue Ridge  
Quickship Available



858  
Oak Grove  
Quickship Available



955  
Centennial  
Quickship Available



969  
Brookwood  
Quickship Available